

Diamana™ DF-SERIES

Low/Mid Launch and Low Spin



We've taken two of our most proven, time tested tour proven profiles – Blue Board and White Board, and Mitsubishi Chemical's latest design and material innovations, to create the Diamana™ DF-Series. The Diamana™ DF-Series uses strategically positioned DIALEAD™ Pitch Fiber, and an incredibly strong hybrid prepreg that combines Mitsubishi Chemical's MR70 – a carbon fiber material that is 20% stronger and has 10% higher modulus than conventional carbon fibers, with boron fibers to create our newest lower launching, stiff-tip profile.

Strength, stability, and performance has a new name – Diamana™ DF-Series.

SHAFT SPECIFICATIONS

| Shaft Name | Flex | Length (in) | Weight (g) | Tip OD (in) | Tip // (in) | Butt OD (in) | Torque (deg) | Kick Point |
|-----------------------|------|-------------|------------|-------------|-------------|--------------|--------------|------------|
| Diamana™ DF-Series 50 | R | 46.0 | 54 | 0.335 | 3.0 | 0.598 | 4.7 | Mid/High |
| Diamana™ DF-Series 50 | S | 46.0 | 58 | 0.335 | 3.0 | 0.606 | 4.6 | Mid/High |
| Diamana™ DF-Series 50 | X | 46.0 | 60 | 0.335 | 3.0 | 0.610 | 4.5 | Mid/High |
| Diamana™ DF-Series 60 | R | 46.0 | 60 | 0.335 | 3.0 | 0.600 | 3.8 | Mid/High |
| Diamana™ DF-Series 60 | S | 46.0 | 64 | 0.335 | 3.0 | 0.606 | 3.8 | Mid/High |
| Diamana™ DF-Series 60 | X | 46.0 | 66 | 0.335 | 3.0 | 0.608 | 3.8 | Mid/High |
| Diamana™ DF-Series 60 | TX | 46.0 | 69 | 0.335 | 3.0 | 0.612 | 3.8 | Mid/High |
| Diamana™ DF-Series 70 | S | 46.0 | 73 | 0.335 | 3.0 | 0.608 | 3.1 | Mid/High |
| Diamana™ DF-Series 70 | X | 46.0 | 77 | 0.335 | 3.0 | 0.612 | 3.1 | Mid/High |
| Diamana™ DF-Series 70 | TX | 46.0 | 79 | 0.335 | 3.0 | 0.614 | 2.9 | Mid/High |
| Diamana™ DF-Series 80 | S | 46.0 | 83 | 0.335 | 3.0 | 0.608 | 3.0 | Mid/High |
| Diamana™ DF-Series 80 | X | 46.0 | 86 | 0.335 | 3.0 | 0.612 | 3.0 | Mid/High |
| Diamana™ DF-Series 80 | TX | 46.0 | 88 | 0.335 | 3.0 | 0.614 | 2.9 | Mid/High |

INSTALLATION | TIP TRIMMING INSTRUCTIONS

| Driver | 3 Wood | 5 Wood | 7 Wood | 9 Wood |
|--------|--------|--------|--------|--------|
| 0" | 0.5" | 0.75" | 1.0" | 1.0" |

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our [dealer locator](#).